b) Amendments to the Claims

Claims 17-19, 22-24, 30, 31, 34 and 35 are currently amended. A detailed listing of all the claims that are or were in the application follows.

Claims 1-16 (Cancelled)

--17. (Currently Amended) An excimer laser comprising: a gas supply structure including a first port serving as a first fluid inlet and a second fluid outlet, a second port serving as a second fluid inlet and a first fluid outlet and a throat portion provided between the first and second ports fluid inlet and the fluid outlet, wherein the first and second ports are symmetric with respect to the throat portion as a center;

a gas supplier <u>capable of for supplying a laser gas into the gas supply</u>
structure <u>in two directions</u> to the fluid inlet such that a flow speed of the laser gas <u>supplied</u>
in either of said two directions is less than a speed of second at the throat portion; and
a waveguide unit having a plurality of slots, for guiding microwaves

into the gas supply structure through the plurality of slots, to excite the laser gas.

- 18. (Currently Amended) The excimer laser according to claim 17, further comprising a circulation system for circulating said laser gas flowing out of one of said fluid outlets, into the other of said fluid inlets.
- 19. (Currently Amended) The excimer laser according to claim 17, wherein said gas supply path structure being arranged so that a ratio of a pressure at one of

said fluid inlets to a pressure at the other of said fluid outlets is not less than a ratio of critical pressures.

- 20. (Previously Presented) The excimer laser according to claim 17, wherein said laser gas is an excimer laser gas which is a mixture of F_2 gas with at least one inert gas selected from Kr, Ar, Ne, and He.
- 21. (Previously Presented) The excimer laser according to claim 17, wherein said gas supply path structure for supplying said laser gas, said gas supply path structure being a structure without an inflection point.
- 22. (Currently Amended) The excimer laser according to claim 17, wherein further comprising at least one pressure correcting means for correcting a pressure at said <u>first port fluid inlet</u> or at said <u>second port fluid outlet</u>.
- 23. (Currently Amended) The excimer laser according to claim 17, further comprising at least one temperature correcting means for correcting a temperature at said <u>first port fluid inlet</u> or at said <u>second port fluid outlet</u>.
- 24. (Currently Amended) The excimer laser according to claim 23, wherein said temperature correcting means has a cooling function and wherein said cooling is effected near said port acting as said fluid outlet.

- 25. (Previously Pesented) The excimer laser according to claim 17, wherein said gas supply path structure further comprising vertical width adjusting means for adjusting a vertical width of said throat portion.
- 26. (Previously Presented) The excimer laser according to claim 18, wherein said circulation system is comprised of at least one bellows pump.
- 27. (Previously Presented) The excimer laser according to claim 18, wherein said circulation system is comprised of at least one circulating pump.
- 28. (Previously Presented) The excimer laser according to claim 18, wherein said circulation system is comprised of at least one blower.
- 29. (Previously Presented) The excimer laser according to claim 18, wherein said circulation system is comprised of at least one fan.
- 30. (Currently Amended) An excimer laser comprising: a gas supply path structure group including a first port serving as a first fluid inlet and a second fluid outlet, a second port serving as a second fluid inlet and a first fluid outlet and a throat portion provided between the first and second ports fluid inlet and the fluid outlet, wherein the first and second ports are symmetric with respect to the throat portion as a center;

a gas supplier <u>capable of</u> supplying a laser gas to the <u>first or second</u> fluid inlet; and

a waveguide unit having a plurality of slots, for guiding microwaves into the gas supply path structure group through the plurality of slots, to excite the laser gas wherein said gas supply path structure group includes a light emitting portion for generating a laser beam, and the flow speed of said laser gas at said light emitting portion is higher than a speed of sound.

- 31. (Currently Amended) The excimer laser according to claim 30, further comprising a circulation system for circulating said laser gas flowing out of <u>said</u> port acting as a fluid outlet of said gas supply path structure group, into <u>said port acting as</u> a fluid inlet of said gas supply path structure group.
- 32. (Previously presented) The excimer laser according to claim 30, wherein said laser gas is an excimer laser gas which is a mixture of F_2 gas with at least one inert gas selected from Kr, Ar, Ne, and He.
- 33. (Previously Presented) The excimer laser according to claim 30, wherein said gas supply path structure group being a structure without an inflection point.
- 34. (Currently Amended) The excimer laser according to claim 30, further comprising at least one pressure correcting means for correcting a pressure at <u>said</u> port acting as a fluid inlet of said gas supply path structure group or at <u>said port acting as</u> a fluid outlet of said gas supply path structure group.

- 35. (Currently Amended) The excimer laser according to claim 30, further comprising at least one temperature correcting means for correcting a temperature at said port acting as a fluid inlet of said gas supply path structure group or at said port acting as a fluid outlet of said gas supply path structure group.
- 36. (Previously Presented) The excimer laser according to claim 30, further comprising vertical width adjusting means for adjusting a vertical width of said throat portion.
- 37. (Previously Presented) The excimer laser according to claim 31, wherein said circulation system is comprised of at least one bellows pump.
- 38. (Previously Presented) The excimer laser according to claim 31, wherein said circulation system is comprised of at least one circulating pump.
- 39. (Previously Presented) The excimer laser according to claim 31, wherein said circulation system is comprised of at least one blower.
- 40. (Previously Presented) The excimer laser according to claim 31, wherein said circulation system is comprised of at least one fan.--

Claims 41-44 (Cancelled)